

Lubricator King Distributions C.C.

Email: sales@LubricatorKing.com

Phone us: 082-455-6886

Fax: 086-671-0594

Web: www.LubricatorKing.com



®

Grease Specification : High Temperature Grease

Product Code 002

Meguin Megol Hochtemperaturfett (High temp grease) PH KP2P-30

Application High temperature applications. Shear stable grease suitable for use over a wide temperature range. Suitable for fans, pumps, electric motors etc. Outstanding friction & wear reduction. Excellent for use with bearings subject to chemicals.

Characteristic	Standard	Unit	Value
Color			Brown
NLGI Class	DIN 51818		1 / 2
Worked Penetration	DIN 51804	0.1mm	300
Base			Polyurea
Base Oil			Mineral Oil
Base Oil viscosity @ 40°C		cST	140
DN factor			400,000
Temperature range		°C	-20 - +150, short periods to 170
Drop point	DIN 51801	Degrees C	215
Working Stability	DIN 51804	0.1mm	max +30
Corrosion protection	DIN 51802	rating	0
Water resistance (absorption)	DIN ISO 3733	g/100 g	< 0.1
Water resistance	DIN 518907 part 1		1-90
DIN Standard	KH2R		

This information is based on information supplied by the lubricant manufacturer and whilst it has been carefully prepared and may be considered reliable it is only advisory.